## DRAFT/10th\_October,2016

The following draft notification, which the Central Government proposes to issue under the Environment (Protection) Act, 1986 (29 of 1986), is hereby published for the information of public likely to be affected thereby; and the notice is hereby given that the said draft notification shall be taken into consideration on or after the expiry of a period of thirty days from the date on which this draft has been made available to public through this website. The comments may be sent to Member Secretary, CPCB and Mr. Dinesh Runiwal, JD (CP) at **adaba.cpcb@nic.in** and **d.runiwal@gov.in** 

## [To be published in the Gazette of India, Extraordinary, Part II, Section 3, Sub-section (i)] GOVERNMENT OF INDIA MINISTRY OF ENVIRONMENT, FOREST AND CLIMATE CHANGE NOTIFICATION New Delhi, the ......, 2016

G.S.R.---- In exercise of the powers conferred by Sections 6 and 25 of the Environment (Protection) Act, 1986 (29 of 1986), the Central Government hereby makes the following rules further to amend the Environment (Protection) Rules, 1986, namely:-

- 1. (1) These rules may be called the Environment (Protection)--- Amendment Rules, 2016
  - (2) They shall come into force on the date of their publication in the Official Gazette.
- 2. In the Environment (Protection) Rules, 1986, in Schedule-I,
  - a) the serial number 16 and the entries relating thereto shall be omitted, and
  - b) for serial number 57 and the entries relating thereto, the following serial number serial number and entries shall be substituted, namely:-

## STANDARDS FOR DISCHARGE OF EFFLUENTS FROM TANNERY INDUSTRY

S. No.	Industry	Parameter	Standards	
			(applicable for all modes of disposal*)	
1	2	3	4	
57	Tanneries	Treated Effluent	Max. permissible values	
			(in mg/l, except for pH)	
		рН	6 to 9	
		Biochemical Oxygen Demand	30	
		(BOD₃ at 27 °C)		
		Chemical Oxygen Demand (COD)	250	
		Total Suspended Solids (TSS)	100	
		Fixed Dissolved Solids (FDS)	2100**	
		Total Chromium	2	
		Sulphides (as S)	2	
		Ammonical-Nitrogen (as N)	50	
		Total Kjeldahl Nitrogen (TKN)	50	
		Notes:		

<ul> <li>recipient system.</li> <li>**Standards for FDS shall not be applicable in case of marine disposal through proper marine outfall.</li> <li>The treated effluent shall be allowed to be discharged in the ambient environment only after exhausting options for reuse in industrial process / irrigation in order to minimise freshwater usage.</li> <li>Any tannery unit attached with the CETPs shall achieve the inlet and treated effluent quality standards as per notification S.O.4(E) dated 1st January 2016 of Environment (Protection) Rules, 1986 and shall also be jointly and severally responsible for ensuring compliance.</li> <li>The standalone MSMEs shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.</li> <li>The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre is not exceeded in the treated effluent.</li> </ul>				
<ul> <li>recipient system.</li> <li>**Standards for FDS shall not be applicable in case of marine disposal through proper marine outfall.</li> <li>The treated effluent shall be allowed to be discharged in the ambient environment only after exhausting options for reuse in industrial process / irrigation in order to minimise freshwater usage.</li> <li>Any tannery unit attached with the CETPs shall achieve the inlet and treated effluent quality standards as per notification S.O.4(E) dated 1st January 2016 of Environment (Protection) Rules, 1986 and shall also be jointly and severally responsible for ensuring compliance.</li> <li>The standalone MSMEs shall meet prescribed discharge norms.</li> <li>The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.</li> <li>The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre is not exceeded in the treated effluent.</li> <li>In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage.</li> <li>Wastewater generation (per tonne of hide processed):         <ul> <li>-Raw-to-Wet Blue process</li> <li>18 m<sup>3</sup>/ton</li> </ul> </li> </ul>		1. *In case of direct disposal into rivers and lakes, the CPCB or SPCB / PCC		
<ul> <li>2. **Standards for FDS shall not be applicable in case of marine disposal through proper marine outfall.</li> <li>3. The treated effluent shall be allowed to be discharged in the ambient environment only after exhausting options for reuse in industrial process / irrigation in order to minimise freshwater usage.</li> <li>4. Any tannery unit attached with the CETPs shall achieve the inlet and treated effluent quality standards as per notification S.O.4(E) dated 1st January 2016 of Environment (Protection) Rules, 1986 and shall also be jointly and severally responsible for ensuring compliance.</li> <li>5. The standalone MSMEs shall meet prescribed discharge norms.</li> <li>6. The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.</li> <li>7. The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre shall be permitted provided the maximum timit of sillo milligramme per litre is not exceeded in the treated effluent.</li> <li>8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.</li> <li>Wastewater generation (per tonne of hide processed):         <ul> <li>Raw-to-Wet Blue process</li> <li>18 m<sup>3</sup>/ton</li> <li>10 m<sup>3</sup>/ton</li> </ul> </li> </ul>		may specify more stringent standards depending upon the quality of the		
<ul> <li>through proper marine outfall.</li> <li>3. The treated effluent shall be allowed to be discharged in the ambient environment only after exhausting options for reuse in industrial process / irrigation in order to minimise freshwater usage.</li> <li>4. Any tannery unit attached with the CETPs shall achieve the inlet and treated effluent quality standards as per notification S.O.4(E) dated 1st January 2016 of Environment (Protection) Rules, 1986 and shall also be jointly and severally responsible for ensuring compliance.</li> <li>5. The standalone MSMEs shall meet prescribed discharge norms.</li> <li>6. The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.</li> <li>7. The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent.</li> <li>8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.</li> <li>Wastewater generation (per tonne of hide processed):         <ul> <li>-Raw-to-Wet Blue process</li> <li>18 m<sup>3</sup>/ton</li> <li>-Wet Blue-to-Finished process</li> </ul> </li> </ul>		recipient system.		
<ul> <li>3. The treated effluent shall be allowed to be discharged in the ambient environment only after exhausting options for reuse in industrial process / irrigation in order to minimise freshwater usage.</li> <li>4. Any tannery unit attached with the CETPs shall achieve the inlet and treated effluent quality standards as per notification S.O.4(E) dated 1st January 2016 of Environment (Protection) Rules, 1986 and shall also be jointly and severally responsible for ensuring compliance.</li> <li>5. The standalone MSMEs shall meet prescribed discharge norms.</li> <li>6. The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.</li> <li>7. The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre is not exceeded in the treated effluent.</li> <li>8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.</li> <li>Wastewater generation (per tonne of hide processed):         <ul> <li>Raw-to-Wet Blue process</li> <li>18 m<sup>3</sup>/ton</li> </ul> </li> </ul>		2. **Standards for FDS shall not be applicable in case of marine d		
<ul> <li>environment only after exhausting options for reuse in industrial process / irrigation in order to minimise freshwater usage.</li> <li>Any tannery unit attached with the CETPs shall achieve the inlet and treated effluent quality standards as per notification S.O.4(E) dated 1st January 2016 of Environment (Protection) Rules, 1986 and shall also be jointly and severally responsible for ensuring compliance.</li> <li>The standalone MSMEs shall meet prescribed discharge norms.</li> <li>The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.</li> <li>The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent.</li> <li>In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.</li> <li>Wastewater generation (per tonne of hide processed):         <ul> <li>Raw-to-Wet Blue process</li> <li>18 m<sup>3</sup>/ton</li> <li>Um<sup>3</sup>/ton</li> </ul> </li> </ul>		through proper marine outfall.		
irrigation in order to minimise freshwater usage.         4. Any tannery unit attached with the CETPs shall achieve the inlet and treated effluent quality standards as per notification S.O.4(E) dated 1st January 2016 of Environment (Protection) Rules, 1986 and shall also be jointly and severally responsible for ensuring compliance.         5. The standalone MSMEs shall meet prescribed discharge norms.         6. The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.         7. The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre is not exceeded in the treated effluent.         8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):       -Raw-to-Wet Blue process         -Raw-to-Wet Blue process       18 m <sup>3</sup> /ton         -Wet Blue-to-Finished process       10 m <sup>3</sup> /ton		3. The treated effluent shall be allowed to be discharged in the amb		
<ul> <li>4. Any tannery unit attached with the CETPs shall achieve the inlet and treated effluent quality standards as per notification S.O.4(E) dated 1st January 2016 of Environment (Protection) Rules, 1986 and shall also be jointly and severally responsible for ensuring compliance.</li> <li>5. The standalone MSMEs shall meet prescribed discharge norms.</li> <li>6. The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.</li> <li>7. The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent.</li> <li>8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.</li> <li>Wastewater generation (per tonne of hide processed):         <ul> <li>-Raw-to-Wet Blue process</li> <li>-Wet Blue-to-Finished process</li> </ul> </li> </ul>		environment only after exhausting options for reuse in industrial process		
<ul> <li>treated effluent quality standards as per notification S.O.4(E) dated 1st January 2016 of Environment (Protection) Rules, 1986 and shall also be jointly and severally responsible for ensuring compliance.</li> <li>The standalone MSMEs shall meet prescribed discharge norms.</li> <li>The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.</li> <li>The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent.</li> <li>In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.</li> <li>Wastewater generation (per tonne of hide processed):         <ul> <li>-Raw-to-Wet Blue process</li> <li>18 m<sup>3</sup>/ton</li> </ul> </li> </ul>		irrigation in order to minimise freshwater usage.		
January 2016 of Environment (Protection) Rules, 1986 and shall also be jointly and severally responsible for ensuring compliance.         5. The standalone MSMEs shall meet prescribed discharge norms.         6. The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.         7. The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent.         8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):       -Raw-to-Wet Blue process       18 m <sup>3</sup> /ton         . Wet Blue-to-Finished process       10 m <sup>3</sup> /ton		4. Any tannery unit attached with the CETPs shall achieve the inlet a		
jointly and severally responsible for ensuring compliance. 5. The standalone MSMEs shall meet prescribed discharge norms. 6. The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas. 7. The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre, a maximum contribution up to 1000 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent. 8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage. Wastewater generation (per tonne of hide processed): -Raw-to-Wet Blue process -Wet Blue-to-Finished process 18 m <sup>3</sup> /ton				
<ul> <li>5. The standalone MSMEs shall meet prescribed discharge norms.</li> <li>6. The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.</li> <li>7. The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent.</li> <li>8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.</li> <li>Wastewater generation (per tonne of hide processed):         <ul> <li>-Raw-to-Wet Blue process</li> <li>Wastewater generation (per tonne of hide processed):</li> <li>-Raw-to-Wet Blue process</li> </ul> </li> </ul>				
<ul> <li>6. The standalone large scale units shall meet prescribed discharge norms; however, CPCB or SPCB / PCC with the approval of CPCB, may mandate ZLD in Large scale units in environmentally sensitive / critical areas.</li> <li>7. The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent.</li> <li>8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.</li> <li>Wastewater generation (per tonne of hide processed): <ul> <li>-Raw-to-Wet Blue process</li> <li>-Wet Blue-to-Finished process</li> </ul> </li> </ul>		jointly and severally responsible for ensuring compliance.		
however, CPCB or SPCB / PCC with the approval of CPCB, may mandate         ZLD in Large scale units in environmentally sensitive / critical areas.         7. The TDS limit with respect to treated effluent shall be 2100 milligramme         per litre; however, in case where TDS in intake water is above 1100         milligramme per litre, a maximum contribution up to 1000 milligramme per         litre shall be permitted provided the maximum limit of 3100 milligramme         per litre is not exceeded in the treated effluent.         8. In case of discharge of treated effluent on land for irrigation, the impact on         soil and groundwater quality shall be monitored twice a year (pre- and         post- monsoon) by the tannery unit. The mixing ratio with sewage shall be         prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):         -Raw-to-Wet Blue process         -Wet Blue-to-Finished process		5. The standalone MSMEs shall meet prescribed discharge norms.		
ZLD in Large scale units in environmentally sensitive / critical areas.         7. The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre, a maximum contribution up to 1000 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent.         8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):       -Raw-to-Wet Blue process       18 m³/ton 10 m³/ton		6. The standalone large scale units shall meet prescribed discharge nor		
<ul> <li>7. The TDS limit with respect to treated effluent shall be 2100 milligramme per litre; however, in case where TDS in intake water is above 1100 milligramme per litre, a maximum contribution up to 1000 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent.</li> <li>8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.</li> <li>Wastewater generation (per tonne of hide processed): <ul> <li>-Raw-to-Wet Blue process</li> <li>Wet Blue-to-Finished process</li> <li>18 m<sup>3</sup>/ton</li> </ul> </li> </ul>		however, CPCB or SPCB / PCC with the approval of CPCB, may	/ mandate	
per litre; however, in case where TDS in intake water is above 1100         milligramme per litre, a maximum contribution up to 1000 milligramme per         litre shall be permitted provided the maximum limit of 3100 milligramme         per litre is not exceeded in the treated effluent.         8. In case of discharge of treated effluent on land for irrigation, the impact on         soil and groundwater quality shall be monitored twice a year (pre- and         post- monsoon) by the tannery unit. The mixing ratio with sewage shall be         prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):         -Raw-to-Wet Blue process       18 m³/ton         -Wet Blue-to-Finished process       10 m³/ton		ZLD in Large scale units in environmentally sensitive / critical areas.		
milligramme per litre, a maximum contribution up to 1000 milligramme per litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent.         8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):       -Raw-to-Wet Blue process       18 m³/ton 10 m³/ton		7. The TDS limit with respect to treated effluent shall be 2100 milligramme		
litre shall be permitted provided the maximum limit of 3100 milligramme per litre is not exceeded in the treated effluent.         8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):       -Raw-to-Wet Blue process       18 m³/ton 10 m³/ton		per litre; however, in case where TDS in intake water is above 1100		
per litre is not exceeded in the treated effluent.         8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):         -Raw-to-Wet Blue process       18 m³/ton         -Wet Blue-to-Finished process       10 m³/ton		milligramme per litre, a maximum contribution up to 1000 milligramme per		
8. In case of discharge of treated effluent on land for irrigation, the impact on soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):         -Raw-to-Wet Blue process       18 m³/ton         -Wet Blue-to-Finished process       10 m³/ton		litre shall be permitted provided the maximum limit of 3100 milligramme		
soil and groundwater quality shall be monitored twice a year (pre- and post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):         -Raw-to-Wet Blue process       18 m³/ton         -Wet Blue-to-Finished process       10 m³/ton				
post- monsoon) by the tannery unit. The mixing ratio with sewage shall be prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):         -Raw-to-Wet Blue process       18 m³/ton         -Wet Blue-to-Finished process       10 m³/ton		8. In case of discharge of treated effluent on land for irrigation, the impact on		
prescribed by SPCB for combined discharge of effluent and sewage.         Wastewater generation (per tonne of hide processed):         -Raw-to-Wet Blue process       18 m³/ton         -Wet Blue-to-Finished process       10 m³/ton				
Wastewater generation (per tonne of hide processed):         -Raw-to-Wet Blue process       18 m³/ton         -Wet Blue-to-Finished process       10 m³/ton				
-Raw-to-Wet Blue process 18 m <sup>3</sup> /ton -Wet Blue-to-Finished process 10 m <sup>3</sup> /ton				
-Wet Blue-to-Finished process 10 m <sup>3</sup> /ton				
		'		
-Raw-to- Finished process 28 m³/ton				
		-Raw-to- Finished process 28 m <sup>3</sup> /to	วท	

[F. NO. Q-15017/30/2004-CPW]

(Dr. Rashid Hasan) Adviser

**Note:-** The principal rules were published in the Gazette of India, Extraordinary, Part II, Section 3,Sub-section (i), *vide* number S.O. 844 (E), dated the 19<sup>th</sup> November, 1986 and subsequently amended *vide* the following notifications, namely:-

S.O. 433 (E), dated the  $18^{th}$  April 1987; G.S.R. 176(E), dated the  $2^{nd}$  April, 1996; G.S.R. 97 (E), dated the  $18^{th}$  February, 2009; G.S.R. 149 (E), dated the  $4^{th}$  March , 2009; G.S.R. 543(E), dated the  $22^{nd}$  July,2009; G.S.R. 739 (E), dated the  $9^{th}$  September, 2010; G.S.R. 809(E), dated, the  $4^{th}$  October, 2010, G.S.R. 215 (E), dated the  $15^{th}$  March, 2011; G.S.R. 221(E), dated the  $18^{th}$  March, 2011; G.S.R. 354 (E), dated the  $2^{nd}$  May, 2011; G.S.R. 424 (E), dated the  $1^{st}$  June, 2011; G.S.R. 446 (E), dated the  $13^{th}$  June, 2011; G.S.R. 152 (E), dated the  $16^{th}$  March,

2012; G.S.R. 266(E), dated the 30<sup>th</sup> March, 2012; and G.S.R. 277 (E), dated the 31<sup>st</sup> March, 2012; and G.S.R. 820(E), dated the 9<sup>th</sup> November, 2012; G.S.R. 176 (E), dated the 18<sup>th</sup> March, 2013; G.S.R. 535(E), dated the 7<sup>th</sup> August, 2013; G.S.R. 771(E), dated the 11<sup>th</sup> December, 2013; G.S.R. 2(E), dated the 2<sup>nd</sup> January, 2014; G.S.R. 229 (E), dated the 28<sup>th</sup> March, 2014; G.S.R. 232(E), dated the 31<sup>st</sup> March, 2014; G.S.R. 325(E), dated the 07<sup>th</sup> May, 2014, G.S.R. 612, (E), dated the 25<sup>th</sup> August 2014; G.S.R. 789(E), dated the 11<sup>th</sup> November 2014; S.O. 3305(E), dated the 7<sup>th</sup> December, 2015; S.O.4(E), dated the 1<sup>st</sup> January 2016; G.S.R. 35(E), dated the 14<sup>th</sup> January 2016; G.S.R. 281 (E), dated the 7<sup>th</sup> March, 2016; G.S.R. 496(E), dated 09<sup>th</sup> May, 2016 and lastly amended vide notification G.S.R.497(E), dated 10<sup>th</sup> May, 2016.